



Protecting your interests

1No. Bollard Sleeve sits over 1No. Bollard Unit without compromising the HVM performance. To ensure compliance with BSI PAS 69 and IWA 14 - 2, the distance between each Bollard must be a maximum of 1.2m. This measurement is taken from the inside face of the bollard that sits within the external sleeve at a height of 600mm. Please note the rendered images shown are for visual purposes only. To discuss your requirements please contact our team.

+44(0)1902 499400 bristormtechnical@hill-smith.co.uk

Product	Bollard Sleeve
Material	Stainless Steel/Mild Steel
Finish	Stainless Steel/Galvanized/PPC/Plascoat
Design	Dome/Flat/Mitre
Branding	Please specify your requirements
Applied to	Impeder Bollards/ Stopper Bollards
Dimensions	Core Specific
1No. Bollard Unit	1No. Sleeve Unit
Installation	Bolted down/ Cast-in to 100mm finish

Standard RAL Colours Available
Traffic Black RAL 9017
Graphite Grey RAL 7024
Traffic Yellow RAL 1023
Traffic White RAL 9016
Traffic Green RAL 6024

This drawing is Copyright © of Hill & Smith Ltd and protected under UK and International law. All rights reserved. This drawing may not be copied in whole or in part or used for any other purpose other than for that which it is supplied without express written consent from the company.





Bollard design variations include: Mitre, Flat and a Dome top, each available with none, one or two reflective strips. Please specify these requirements when requesting a quotation.

	Galvanised	Stainless Steel	Powder Coat (PCC)	Plascoat
Erosion protection	<b>✓</b>	✓	✓	✓
Smooth finish on corners and edges	*	<b>√</b>	*	✓
Multiple colours available	×	*	<b>√</b>	✓
Crack and peel resistance	×	*	×	✓
Retouched without need to remove & re-coat	*	×	<b>√</b>	✓
Additional aesthetics available	✓	✓	✓	✓

hillmith	Hill & Smith Ltd Spri Business & Industrial Park Bi Wolverhampton, WV14 0QL.		ark Bilston,
Date 03/08/2018	R	evision A	Sheet 1 /1