

PEDESTRIAN GUARDRAIL

FOR IMPEDER/STOPPER BOLLARDS



1No. Pedestrian Guardrail sits over 2No. Bollard Units without compromising the HVM performance. To ensure compliance with BSI PAS 69 and IWA 14 - 2, the distance between each Bollard must be a maximum of 1.2m. This measurement is taken from the inside face of the bollard that sits within the external sleeve at a height of 600mm. Please note the rendered images shown are for visual purposes only. To discuss your requirements please contact our team.

+44(0)1902 499400
 bristormtechnical@hill-smith.co.uk

Product	Pedestrian Guardrail
Material	Stainless Steel/Mild Steel
Finish	Stainless Steel/Galvanized/PPC/Plascoat
Design	Contact us to discuss arrangement details
Branding	Please specify your requirements
Applied to	Impeder Bollards/ Stopper Bollards
Dimensions	Core Specific
2No. Bollard Units	1No. Sleeve Unit
Installation	Bolted down/ Cast-in to 100mm finish

Standard RAL Colours Available
Traffic Black RAL 9017
Graphite Grey RAL 7024
Traffic Yellow RAL 1023
Traffic White RAL 9016
Traffic Green RAL 6024



	Galvanised	Stainless Steel	Powder Coat (PCC)	Plascoat
Erosion protection	✓	✓	✓	✓
Smooth finish on corners and edges	✗	✓	✗	✓
Multiple colours available	✗	✗	✓	✓
Crack and peel resistance	✗	✗	✗	✓
Retouched without need to remove & re-coat	✗	✗	✓	✓
Additional aesthetics available	✓	✓	✓	✓

Hill & Smith Ltd
 Springvale Business & Industrial Park
 Bilston, Wolverhampton, WV14 0QL.

Date 03/08/2018	Revision A	Sheet 1 / 1
DOC No.		TR - SF04

www.hill-smith.co.uk - www.bristorm.com

This drawing is Copyright © of Hill & Smith Ltd and protected under UK and International law. All rights reserved. This drawing may not be copied in whole or in part or used for any other purpose other than for that which it is supplied without express written consent from the company.